

Product sheet

RF 868MHZ Store Kit FERMAX 5249

Brand: FERMAX

Reference: FERMAX 5249



RF 868MHZ STORE KIT. This Radio Frequency Kit allows remote door opening through an RF control. At the door, a receiver is required that can be located both indoors (ideal for shops and garages) and outdoors. The remote control has an exclusive code per user that offers maximum security and reaches a distance of up to 100 meters through the 868Mhz frequency band. And thanks to its advanced APS (Approaching System) transmission system, the remote can be activated even when out of range of the receiver. The signal will be transmitted repeatedly for 15 seconds while the user approaches the door and until the moment it is opened. The control includes two buttons that will allow, in addition to opening the door, to activate a second function such as activating or deactivating a light or air conditioning, opening a second door.

[View product online](#)

Description

DESCRIPTION

This Radiofrequency Kit allows the door to be opened remotely through an RF control. On the door, a receiver is required that can be located both inside (ideal for shops and garages) and outside.

The control has an exclusive code per user that offers maximum security and reaches a distance of up to 100 meters through the 868Mhz frequency band. And thanks to its advanced APS (Approaching System) transmission system, the remote can be activated even when out of range of the receiver. The signal will be transmitted repeatedly for 15 seconds while the user approaches the door and until the moment it is opened.

The control includes two buttons that will allow, in addition to opening the door, activate a second function such as activating or deactivating a light or air conditioning, opening a second door ...

The kit includes RF receiver ref. 5250 up to 500 codes, power supply ref. 4802 and 3 KeySingle Mini remote controls ref. 5259.

TECHNICAL SPECIFICATIONS

BASIC-2B
Frequency: 868.35MHz
Coding: High security changing code
Memory: 500 codes
Number of relays: 2 relays (Relay1 (monostable) and Relay 2 (monostable/bistable))
Power supply: 12/24Vac/dc ± 10%
Relay contacts: 1A
Standby/operating consumption: 60mA/90mA
Operating temperature: -20°C to + 85°C
Tightness: IP54 (with IP65 cable gland)
Dimensions: 63x74x25mm
Box dimensions: 82x190x40mm

Weight: 0.900246 kg
Measures of the packed product: 7.5x23x17.8 cm
EAN 13: 8424299052496

Specifications

EAN	8424299052496
Manufacturer	FERMAX

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 24 October 2026