

Product sheet

VDS FERMAX 7415 audio module

Brand: FERMAX

Reference: FERMAX 7415



Amplifier module to be incorporated into Skyline door entry panels. It has volume adjustments, both in the street-house and house-street direction, so that the installer can adjust the optimal level. The line is made up of 8 frames of different sizes where the different modules fit easily, and allow a specific number of modules to be attached. It is possible to combine two or more panels, as long as they are from the same series, to have a greater capacity for buttons and accessories. In replacement, it is possible to make the change from analogue doorphone to video doorphone taking advantage of the existing wiring. The capacity and distance of the system will depend on the installation wiring. The VDS amplifier includes a voice synthesizer as standard.

[View product online](#)

Description

DESCRIPTION Amplifier module to be incorporated into SKYLINE door entry panels. It is the module (speaker unit) that incorporates the electronic circuits Necessary for the operation of the audio system, door opening, etc. .. in the intercom facilities. It has volume adjustments, both in the street-house and house-street direction, so that the installer can adjust the optimal level. The New SKYLINE electronic and video door entry panel is a robust and elegant panel, It stands out for its durability and beauty, resistance and reliability. SKYLINE is the new line of entrance panels for electronic and video entry phones with a continuous profile and modular composition from Fermax. The line is made up of 8 frames of different sizes where the different modules are easily fitted: push buttons, card holder, camera, amplifier, access control, etc. Frames allow a specified number of modules to be attached. There are two sizes of modules: V and W. The W modules are twice the size of the V modules. Module Measurements. - V Module: 105.2x47.5 mm (width-height). - Module W: 105.2x95 mm (width-height). It is possible to combine two or more plates, as long as they are from the same series, to have a greater capacity for pushbuttons and accessories. VDS system: Simplified installation of doorphone and video doorphone system, which does not use call wires per home. The call is made by transmission of a digital call code generated by the VDS amplifier. - In new construction, the installation can be done with the following type of cabling: UTP CAT5/5-Wire/3-wire + Coaxial (video). It allows managing buildings with

up to 199 homes, 2 entrance entrances and a concierge center. Maximum distance from first access to last home: 200 m.

Specifications

EAN	8424299074153
Manufacturer	FERMAX

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 30 September 2026