

Product sheet

FERMAX 7440 proximity reader module

Brand: FERMAX

Reference: FERMAX 7440



Reader that allows the door to be opened by bringing a proximity card or key ring closer. Only authorized cards or key fobs will activate the device and no physical contact is necessary. Reader and controller integrated in the same module. It requires a door controller for its connection and operation. Acoustic and visual confirmation by means of signaling LEDs of the acceptance or rejection of the card presented. Access control module, to be incorporated into Skyline and Cityline door entry/video door entry panels. Recommended for indoors and outdoors.

[View product online](#)

Description

DESCRIPTION * Reader that allows the door to be opened when a proximity card or key ring is brought closer. Only authorized cards or key fobs will activate the device. No physical contact is necessary. * Proximity reader that by means of a dipswitches configuration (SW2) that it incorporates can work in an autonomous or centralized system. Configuration as AUTONOMOUS. * Capacity for up to 400 user cards or key fobs. * Reader and controller integrated in the same module. Configuration as CENTRALIZED MDS-AC Plus. * Proximity reader with capacity for up to: - 1020 user cards/key rings with the MDS central unit (ref. 2405). - 2048 user cards/key rings with the AC Plus central unit (ref. 4410). * Reader and controller integrated in the same module. Configuration as CENTRALIZED with Wiegand 26 or Data/Clock protocol. * When starting the reader if it is in mode: - Wiegand-26, the «+» LED will light for 1 second. - Data/Clock, the «-» LED will light for 1 second. * Proximity reader with capacity up to: - 1020 card User etas/key fobs with the MDS central unit (ref. 2405). - 2048 user cards/key fobs with the AC Plus central unit (ref. 4410). * Requires a door controller (ref. 4420) for connection and operation. * Acoustic and visual confirmation by means of signaling LEDs of the acceptance or rejection of the presented card. * Access control module, to be incorporated into SKYLINE and CITYLINE door entry/video door entry panels. * Recommended for indoors and outdoors. **TECHNICAL SPECIFICATIONS** Technical Characteristics **AUTONOMOUS:** - No requires physical contact reader-card. Reading distance of 5 cm (card) or 1.5 cm (key ring). - Acoustic and visual information on actions. - Very simple manual or PC programming (card registration).

Specifications

EAN	8424299074405
Manufacturer	FERMAX

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 20 October 2026