

Product sheet

LEGRAND 004873 | Unipolar distributor 250A

Brand: LEGRAND

Reference: LEGRAND 004873



UNIPOLAR 250A distributor. Single-pole distributors
 Connection with or without Starfix ferrules
 Glow wire resistance according to EN 60695-2-11: 960°C
 in the active parts Single-pole 1000 V=
 DIN rail mounting
 Equipped of label holders
 I_{max}: 250 A
 Connections by rigid bar: 1 x 70 to 150 4 x 2.5 to 16 6 x
 10 to 35 mm²
 Connections by flexible bar: 1 x 70 to 120 4 x 2.5 to 10 6
 x 10 to 25 mm²
 Max. connectable «solar cell»: 4 x 2.5 to 10, 6 x 10 to 16
 or 3 x 25 mm²
 I_{sc} crest: 60 kA
 Number of modules: 2. Monobloc and associable modular
 distributors
 40 at 250 A
 "Standard" distribution
 Connection with or without Starfix ferrules
 Glow wire resistance according to EN 60695-2-11: 960 °C
 on the supports of the active parts.

[View product online](#)

Specifications

Rated current (A)	250
EAN	3414971439757
Manufacturer	Legrand
No. of poles	1P
Weight (kg)	0

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 3 October 2026