

Product sheet

Automatic circuit breaker iC60N 3P 20A curve-D

Brand: SCHNEIDER

Reference: IMPO A9F75320



iC60N Acti 9 thermal-magnetic circuit breaker, 3P, 20A, curve D, 50/60 Hz, IP20, Thermal-magnetic, Suitable for sectioning, Contact position indicator, Type of control: Handle, Local signaling: Trip indicator, Mode Mounting Bracket: Fixed, Mounting Bracket: DIN Rail, Earth Leakage Protection: Freestanding Block, 85x54x78.5mm, 0.375kg, White. Breaking capacity: 20 kA Icu according to IEC 60947-2, 220...240 V AC 50/60 Hz, 10 kA Icu according to IEC 60947-2, 380...415 V AC 50/60 Hz, 36 kA Icu conforming to IEC 60947-2, 12...133 V AC 50/60 Hz, 36 kA Icu conforming to EN 60947-2, 12...133 V AC 50/60 Hz, 6 kA Icu according to IEC 60947-2, 440 V AC 50/60 Hz, 6000 A Icn according to IEC 60898-1, 400 V AC 50/60 Hz, 20 kA Icu according to EN 60947-2, 220...240 V AC 50/60 Hz, 10 kA Icu according to EN 60947-2, 125...180 V DC, 6000 A Icn according to EN 60898-1, 400 V AC 50/60 Hz, 10 kA Icu according with IEC 60947-2, 125...180 V DC, 10 kA Icu conforming to EN 60947-2, 380...415 V AC 50/60 Hz, 6 kA Icu conforming to EN 60947-2, 440 V AC 50/60 Hz, utilization category: category A according to EN 60947-2, category A according to IEC 60947-2, suitable for isolating: yes according to IEC 60898-1, yes according to EN 60898-1, yes according to EN 60947-2, yes according to IEC 60947-2, standards: IEC 60947-2, IEC 60898-1, EN 60898-1, EN 60947-2.

[View product online](#)

Specifications

Rated current (A)	20
Curve	D
EAN	3606480080838
Manufacturer	Schneider
No. of poles	3P
Reference	SCHNEIDER A9F75320
Cable cross-section (mm ²)	5

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 30 September 2026