Product sheet



Automatic circuit breaker iC60N 4P 6A curve-C

Brand: SCHNEIDER

Reference: SCHNEIDER A9F79406

Circuit breaker iC60N Acti 9, 4P, 6A, curve C, IP20, Thermal-magnetic, Suitable for isolation, Contact position indicator, Type of control: Handle, Local signaling: Trip indicator, Mounting method: Fixed, Mounting bracket: DIN rail, Earth leakage protection: Independent block, 85x72x78.5mm, 0.5kg, White. Breaking capacity: 10 kA Icu according to IEC 60947-2, 380...415 V AC 50/60 Hz, 20 kA Icu according to EN 60947-2, 220...240 V AC 50/60 Hz, 6 kA Icu conforming to EN 60947-2, 440 V AC 50/60 Hz, 10 kA Icu conforming to IEC 60947-2, 180...250 V DC, 36 kA Icu conforming to IEC 60947-2, 12 ...133 V AC 50/60 Hz, 10 kA Icu according to EN 60947-2, 380...415 V AC 50/60 Hz, 36 kA Icu according to EN 60947-2, 12...133 V AC 50/60 Hz, 6000 A Icn according to EN 60898-1, 400 V AC 50/60 Hz, 20 kA Icu according to IEC 60947-2, 220...240 V AC 50/60 Hz, 6000 A Icn conforming to IEC 60898-1, 400 V AC 50/60 Hz, 10 kA Icu conforming to EN 60947-2, 180...250 V DC, 6 kA Icu conforming to IEC 60947-2, 440 V AC 50/60 Hz, utilization category: category A according to IEC 60947-2, category A according to EN 60947-2, suitable for isolating: yes according to IEC 60947-2, yes according to EN 60947- 2, yes according to IEC 60898-1, yes according to EN 60898-1, standards: EN 60898-1, IEC 6 0947-2, IEC60898-1, EN60947-2.

View product online

Specifications

Rated current (A)	6
Curve	C
EAN	3606480093395
Manufacturer	Schneider
No. of poles	4P

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 24 November 2026