

Product sheet

Automatic circuit breaker iC60N 4P 40A curve-D

Brand: SCHNEIDER

Reference: IMPO A9F75440



iC60N Acti thermal-magnetic circuit breaker, 4P, 40A, curve D, 50/60 Hz, IP20, Thermal-magnetic, Suitable for isolation, Contact position indicator, Type of control: Toggle, Local signaling: Trip indicator, Trip mode mounting: Fixed, Mounting bracket: DIN rail, Earth leakage protection: Independent block, 85x72x78.5mm, 0.5kg, White. Breaking capacity: 6000 A Icn according to EN 60898-1, 400 V AC 50/60 Hz, 10 kA Icu according to EN 60947-2, 380...415 V AC 50/60 Hz, 20 kA Icu according to EN 60947-2, 220...240 V AC 50/60 Hz, 10 kA Icu according to EN 60947-2, 180...250 V DC, 6 kA Icu according to IEC 60947-2, 440 V AC 50/60 Hz, 6000 A Icn according to IEC 60898-1, 400 V AC 50/60 Hz, 10 kA Icu according to IEC 60947-2, 380...415 V AC 50/60 Hz, 20 kA Icu conforming to IEC 60947-2, 220...240 V AC 50/60 Hz, 10 kA Icu conforming to IEC 60947-2, 180...250 V DC, 36 kA Icu conforming to IEC 60947-2, 12...133 V AC 50/60 Hz, 6 kA Icu conforming to EN 60947-2, 440 V AC 50/60 Hz, 36 kA Icu conforming to EN 60947-2, 12...133 V AC 50/60 Hz, utilization category: category A according to EN 60947-2, category A according to IEC 60947-2, suitable for isolating: yes according to IEC 60947-2, yes according to EN 60947-2, yes according to IEC 60898-1, yes according to EN 60898-1, standards: EN 60947-2, EN 60898-1, IEC 60898-1, IEC 60947-2.

[View product online](#)

Specifications

Rated current (A)	40
Curve	D
EAN	3606480081224
Manufacturer	Schneider
No. of poles	4P
Reference	SCHNEIDER A9F75440
Cable cross-section (mm ²)	85x72

may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 6 October 2026