Product sheet



Automatic circuit breaker iC60N 4P 40A curve-D

Brand: SCHNEIDER

Reference: IMPO A9F75440

iC60N Acti thermal-magnetic circuit breaker, 4P, 40A, curve D, 50/60 Hz, IP20, Thermal-magnetic, Suitable for isolation, Contact position indicator, Type of control: Toggle, Local signaling: Trip indicator, Trip mode mounting: Fixed, Mounting bracket: DIN rail, Earth leakage protection: Independent block, 85x72x78.5mm, 0.5kg, White. Breaking capacity: 6000 A Icn according to EN 60898-1, 400 V AC 50/60 Hz, 10 kA Icu according to EN 60947-2, 380...415 V AC 50/60 Hz, 20 kA Icu de according to EN 60947-2, 220...240 V AC 50/60 Hz, 10 kA Icu according to EN 60947-2, 180...250 V DC, 6 kA Icu according to IEC 60947-2, 440 V AC 50/60 Hz, 6000 A Icn according to IEC 60898-1, 400 V AC 50/60 Hz, 10 kA Icu according to IEC 60947-2, 380...415 V AC 50/60 Hz, 20 kA Icu conforming to IEC 60947-2, 220...240 V AC 50/60 Hz, 10 kA Icu conforming to IEC 60947-2, 180...250 V DC, 36 kA Icu conforming to IEC 60947- 2, 12...133 V AC 50/60 Hz, 6 kA Icu conforming to EN 60947-2, 440 V AC 50/60 Hz, 36 kA Icu conforming to EN 60947-2, 12...133 V AC 50/60 Hz, utilization category: category A according to EN 60947-2, category A according to IEC 60947-2, suitable for isolating: yes according to IEC 60947-2, yes according to EN 60947- 2, yes according to IEC 60898-1, yes according to EN 60898-1, standards: EN 60947-2, EN 60 898-1, IEC 60898-1, IEC 60947-2.

View product online

Specifications

Rated current (A)	40
Curve	D
EAN	3606480081224
Manufacturer	Schneider
No. of poles	4P
Reference	SCHNEIDER A9F75440
Cable cross-section (mm²)	85x72

This document is based on the product page published in our store and is provided for information only. It is not contractual. It

may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 23 November 2026