Product sheet



Automatic circuit breaker iC60H 2P 25A curve-C

Brand: SCHNEIDER

Reference: SCHNEIDER A9F89225

iC60H Acti 9 thermal-magnetic circuit breaker, 2P, 25A, curve C, IP20, thermal-magnetic, suitable for isolation, contact position indicator, handle control, trip indicator, fixed mounting, DIN rail support, protection against leaks to ground with independent block, measures 85x36x78.5mm, weighs 0.25kg and is white. Breaking capacity: 70 kA Icu according to IEC 60947-2, 220...240 V AC 50/60 Hz, 20 kA Icu according to EN 60947-2, 12...60 V DC, 70 kA Icu of according to EN 60947-2, 12...60 V AC 50/60 Hz, 15 kA Icu according to IEC 60947-2, 72 V DC, 10000 A Icn according to EN 60898-1, 230 V AC 50/60 Hz, 10000 A Icn conforming to IEC 60898-1, 230 V AC 50/60 Hz, 20 kA Icu conforming to IEC 60947-2, 12...60 V DC, 70 kA Icu conforming to EN 60947- 2, 220...240 V AC 50/60 Hz, 15 kA Icu according to EN 60947-2, 72 V DC, 70 kA Icu according to EN 60947-2, 100...133 V AC 50/60 Hz, 70 kA Icu according to IEC 60947-2, 12...60 V AC 50/60 Hz, 70 kA Icu according to IEC 60947-2, 100...133 V AC 50/60 Hz, category of utilization A in accordance with IEC 60947-2, category A in accordance with EN 60947-2, suitable for isolation in accordance with EN 60898-1, in accordance with IEC 60947-2, in accordance with EN 60947-2 and in accordance with IEC60898-1. Standards: IEC 60898-1, IEC 60947-2, EN 60947-2, EN 60898-1.

View product online

Specifications

Rated current (A)	25
Curve	C
EAN	3606480095054
Manufacturer	Schneider
No. of poles	2P

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 24 November 2026