

Product sheet

Automatic circuit breaker iC60H 2P 16A curve-D

Brand: SCHNEIDER

Reference: IMPO A9F85216



iC60H Acti 9 thermal-magnetic circuit breaker, 2P, 16A, curve D, IP20, thermal-magnetic, suitable for isolation, contact position indicator, handle control, trip indicator, fixed mounting, DIN rail support, without leakage protection to ground, measures 85x18x78.5mm, weighs 0.215kg and is white. Breaking capacity: 10000 A Icn conforming to IEC 60898-1, 230 V AC 50/60 Hz, 15 kA Icu conforming to IEC 60947-2, 220...240 V AC 50/60 Hz, 15 kA Icu de according to EN 60947-2, 220...240 V AC 50/60 Hz, 20 kA Icu according to IEC 60947-2, 12...60 V DC, 30 kA Icu according to EN 60947-2, 100 ...133 V AC 50/60 Hz, 10000 A Icn conforming to EN 60898-1, 230 V AC 50/60 Hz, 42 kA Icu conforming to IEC 60947-2, 12...60 V AC 50/60 Hz, 15 kA Icu according to EN 60947-2, 72 V DC, 20 kA Icu according to EN 60947-2, 12...60 V DC, 30 kA Icu according to IEC 60947-2, 100. ..133 V AC 50/60 Hz, 42 kA Icu conforming to EN 60947-2, 12...60 V AC 50/60 Hz, 15 kA Icu conforming to IEC 60947-2, 72 V DC, category of utilization A in accordance with EN 60947-2, category A in accordance with IEC 60947-2, suitable for isolation in accordance with EN 60898-1, in accordance with EN 60947-2, in accordance with IEC 60947-2 and in accordance with IEC60898-1. Standards: IEC 60898-1, EN 60898-1, EN 60947-2, IEC 60947-2.

[View product online](#)

Specifications

Rated current (A)	16
Curve	D
EAN	3606480083129
Manufacturer	Schneider
No. of poles	2P
Weight (kg)	0,25
Reference	SCHNEIDER A9F85216
Cable cross-section (mm²)	85x18

may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 15 September 2026