Product sheet



Automatic circuit breaker iC60H 4P 40A curve-D

Brand: SCHNEIDER

Reference: IMPO A9F85440

iC60H Acti 9 thermal-magnetic circuit breaker, 4P, 40A, curve D, IP20, thermal-magnetic, suitable for isolation, contact position indicator, handle control, trip indicator, fixed mounting, DIN rail support, protection against leaks to ground with independent block, measures 85x72x78.5mm, weighs 0.5kg and is white. Breaking capacity: 15 kA Icu according to EN 60947-2, 380...415 V AC 50/60 Hz, 15 kA Icu according to EN 60947-2, 125...180 V DC, 10000 A Icn of according to IEC 60898-1, 400 V AC 50/60 Hz, 42 kA Icu according to IEC 60947-2, 12...133 V AC 50/60 Hz, 10 kA Icu according to EN 60947-2, 440 V AC 50/60 Hz, 15 kA Icu conforming to IEC 60947-2, 125...180 V DC, 30 kA Icu conforming to IEC 60947-2, 220...240 V AC 50/60 Hz, 42 kA Icu according to EN 60947-2, 12...133 V AC 50/60 Hz, 10000 A Icn according to EN 60898-1, 400 V AC 50/60 Hz, 30 kA Icu according to EN 60947- 2, 220...240 V AC 50/60 Hz, 15 kA Icu conforming to IEC 60947-2, 380...415 V AC 50/60 Hz, 10 kA Icu conforming to IEC 60947-2, 440 V AC 50/60 Hz, utilization category A according to EN 60947-2 and according to IEC 60947-2, suitable for isolating according to EN 60947-2, according to IEC 60947-2, according to EN 60898 -1 and in accordance with IEC 60898-1, standards: IEC 60947-2, IEC 60898-1, EN 60898-1, EN 60947- two.

View product online

Specifications

Rated current (A)	40
Curve	D
EAN	3606480083372
Manufacturer	Schneider
No. of poles	4P
Reference	SCHNEIDER A9F85440

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 25 November 2026