Product sheet



Automatic circuit breaker iC60N 1P 25A curve-C

Brand: SCHNEIDER

Reference: SCHNEIDER A9F79125

Circuit breaker iC60N Acti 9, 1P, 25A, curve C, IP20, 6000A Icn according to EN 60898-1, 230V AC 50/60Hz, thermal-magnetic, suitable for sectioning, contact position indicator, handle control, trip indicator, fixed mounting, DIN rail support, without protection against earth leakage, measures 85x18x78.5mm, weighs 0.215kg and is white. Breaking capacity: 15 kA Icu according to EN 60947-2, 12...60 V DC, 10 kA Icu according to EN 60947-2, 220...240 V AC 50/60 Hz, 36 kA Icu of according to IEC 60947-2, 12...60 V AC 50/60 Hz, 20 kA Icu according to EN 60947-2, 100...133 V AC 50/60 Hz, 10 kA Icu according to EN 60947 -2, 72 V DC, 20 kA Icu conforming to IEC 60947-2, 100...133 V AC 50/60 Hz, 10 kA Icu conforming to IEC 60947-2, 220...240 V AC 50/60 Hz, 15 kA Icu conforming to IEC 60947-2, 12...60 V DC, 36 kA Icu conforming to EN 60947-2, 12...60 V AC 50/60 Hz, 10 kA Icu conforming with IEC 60947-2, 72 V DC, 6000 A Icn according to IEC 60898-1, 230 V AC 50/60 Hz, 6000 A Icn according to EN 60898-1, 230 V AC 50/60 Hz, category of use A according to EN 60947-2 and IEC 60947-2, suitable for isolation according to EN 60898-1, IEC 60898-1, EN 60947-2 and IEC 60947-2, standards: EN 60898-1, EN 60947 -2, IEC 60898-1 and IEC 60947-2.

View product online

Specifications

Rated current (A)	25
Curve	C
EAN	3606480093166
Manufacturer	Schneider
No. of poles	1P
Weight (kg)	0,215

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 24 November 2026