

Product sheet

Automatic circuit breaker iC60N 1P+N 6A curve-C

Brand: SCHNEIDER

Reference: SCHNEIDER A9F79606



iC60N Acti 9 thermal-magnetic circuit breaker, 1P+N, 6A, curve C, IP20, thermal-magnetic, suitable for isolation, contact position indicator, handle control, trip indicator, fixed mounting, DIN rail support, protection against ground leakage with independent block, measures 85x36x78.5mm, weighs 0.25kg and is white. Breaking capacity: 20 kA Icu according to IEC 60947-2, 100...133 V AC 50/60 Hz, 10 kA Icu according to IEC 60947-2, 220...240 V AC 50/60 Hz, 10 kA Icu conforming to EN 60947-2, 220...240 V AC 50/60 Hz, 6000 A Icn conforming to IEC 60898-1, 230 V AC 50/60 Hz, 36 kA Icu conforming to IEC 60947 -2, 12...60 V AC 50/60 Hz, 6000 A Icn according to EN 60898-1, 230 V AC 50/60 Hz, 20 kA Icu according to EN 60947-2, 100...133 V AC 50/60 Hz, 36 kA Icu conforming to EN 60947-2, 12...60 V AC 50/60 Hz, utilization category A conforming to IEC 60947-2 and EN 60947-2, suitable for isolating according to EN 60898-1, IEC 60947-2, IEC 60898-1 and EN 60947-2, standards: EN 60898-1, IEC 60947-2, IEC 60898-1 and EN 60947-2.

[View product online](#)

Specifications

Rated current (A)	6
Curve	C
EAN	3606480093487
Manufacturer	Schneider
No. of poles	1P+N

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 7 October 2026