Product sheet



Automatic circuit breaker iC60N 2P 6A curve-C

Brand: SCHNEIDER

Reference: SCHNEIDER A9F79206

Circuit breaker iC60N Acti 9, 2P, 6A, curve C, IP20, 6kA Icn in accordance with IEC 60947-2, 440V AC 50/60Hz, thermal-magnetic, Suitable for isolation. Contact position indicator. Control Type: Lever. Local signals: Trip indicator. Mounting mode: Fixed. Mounting support: DIN rail. Earth leakage protection: Independent block, 85x36x78.5mm, 0.25kg, White. Breaking capacity: 6000 A Icn according to EN 60898-1, 400 V AC 50/60 Hz, 10 kA Icu according to EN 60947-2, 380.415 V AC 50/60 Hz, 20 kA Icu according to EN 60947 -2, 220.240 V AC 50/60 Hz, 6 kA Icu according to EN 60947-2, 440 V AC 50/60 Hz, 36 kA Icu according to EN 60947-2, 12.133 V AC 50/60 Hz, 10 kA Icu according to IEC 60947-2, 380.415 V AC 50/60 Hz, 10 kA Icu according to IEC 60947-2, 72.125 V DC, 36 kA Icu according to IEC 60947-2, 12.133 V AC 50/60 Hz, 10 kA Icu according to EN 60947-2, 72.125 V DC, 6000 A Icn according to IEC 60898-1, 400 V AC 50/60 Hz, 6 kA Icu according to IEC 60947-2, 440 V AC 50/60 Hz, 20 kA Icu according to IEC 60947-2, 220.240 V AC 50/60 Hz, utilization category: category A according to IEC 60947-2, category A according to EN 60947-2, suitable for isolating: yes according to EN 60947-2, yes according to EN 60898-1, yes according to IEC 60947-2, yes according to IEC 60898-1, standards: IEC 60947-2, EN 60947-2, EN60898-1 ,IEC60898-1.

View product online

Specifications

Rated current (A)	6
Curve	C
EAN	3606480093210
Manufacturer	Schneider
No. of poles	2P

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 25 November 2026