

Product sheet

Automatic circuit breaker iC60N 2P 6A curve-C

Brand: SCHNEIDER

Reference: SCHNEIDER A9F79206



Circuit breaker iC60N Acti 9, 2P, 6A, curve C, IP20, 6kA Icn in accordance with IEC 60947-2, 440V AC 50/60Hz, thermal-magnetic, Suitable for isolation. Contact position indicator. Control Type: Lever. Local signals: Trip indicator. Mounting mode: Fixed. Mounting support: DIN rail. Earth leakage protection: Independent block, 85x36x78.5mm, 0.25kg, White. Breaking capacity: 6000 A Icn according to EN 60898-1, 400 V AC 50/60 Hz, 10 kA Icu according to EN 60947-2, 380.415 V AC 50/60 Hz, 20 kA Icu according to EN 60947 -2, 220.240 V AC 50/60 Hz, 6 kA Icu according to EN 60947-2, 440 V AC 50/60 Hz, 36 kA Icu according to EN 60947-2, 12.133 V AC 50/60 Hz, 10 kA Icu according to IEC 60947-2, 380.415 V AC 50/60 Hz, 10 kA Icu according to IEC 60947-2, 72.125 V DC, 36 kA Icu according to IEC 60947-2, 12.133 V AC 50/60 Hz, 10 kA Icu according to EN 60947-2, 72.125 V DC, 6000 A Icn according to IEC 60898-1, 400 V AC 50/60 Hz, 6 kA Icu according to IEC 60947-2, 440 V AC 50/60 Hz, 20 kA Icu according to IEC 60947-2, 220.240 V AC 50/60 Hz, utilization category: category A according to IEC 60947-2, category A according to EN 60947-2, suitable for isolating: yes according to EN 60947-2, yes according to EN 60898-1, yes according to IEC 60947-2, yes according to IEC 60898-1, standards: IEC 60947-2, EN 60947-2, EN60898-1 ,IEC60898-1.

[View product online](#)

Specifications

Rated current (A)	6
Curve	C
EAN	3606480093210
Manufacturer	Schneider
No. of poles	2P

If you have any questions, contact our support team

Item downloaded on 11 October 2026