

Product sheet

Automatic circuit breaker iC60N 3P 6A curve-C

Brand: SCHNEIDER

Reference: SCHNEIDER A9F79306



Circuit breaker iC60N Acti 9, 3P, 6A, curve C, IP20, Thermal-magnetic, Suitable for isolation, Contact position indicator, Type of control: Handle, Local signaling: Trip indicator, Mounting mode: Fixed, Mounting bracket: DIN rail, Earth leakage protection: Independent block, 85x54x78.5mm, 0.375kg, White. Breaking capacity: 6 kA Icu in accordance with IEC 60947-2, 440 V AC 50/60 Hz, 20 kA Icu in accordance with EN 60947-2, 220...240 V AC 50/60 Hz, 10 kA Icu in accordance with EN 60947-2, 380...415 V AC 50/60 Hz, 36 kA Icu according to IEC 60947-2, 12...133 V AC 50/60 Hz, 20 kA Icu according to IEC 60947-2, 220...240 V AC 50/60 Hz, 6000 A Icn according to EN 60898-1, 400 V AC 50/60 Hz, 6 kA Icu according to EN 60947-2, 440 V AC 50/60 Hz, 10 kA Icu according to EN 60947-2, 125...180 V DC, 36 kA Icu according to EN 60947-2, 12...133 V AC 50/60 Hz, 10 kA Icu according to IEC 60947-2, 380...415 V AC 50/60 Hz, 6000 A Icn according to IEC 60898-1, 400 V AC 50/60 Hz, 10 kA Icu according to IEC 60947-2, 125...180 V DC, utilization category: category A in accordance with IEC 60947-2, category A in accordance with EN 60947-2, suitable for isolating: yes in accordance with EN 60947-2, yes in accordance with IEC 60947-2, yes according to IEC 60898-1, yes according to EN 60898-1, standards: EN 60947-2, EN 60898-1, IEC 60947-2, IEC 60898-1.

[View product online](#)

Specifications

Rated current (A)	6
Curve	C
EAN	3606480093302
Manufacturer	Schneider
No. of poles	3P
Weight (kg)	0,375

may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 30 September 2026