Product sheet



Automatic circuit breaker iC60N 3P 6A curve-C

Brand: SCHNEIDER

Reference: SCHNEIDER A9F79306

Circuit breaker iC60N Acti 9, 3P, 6A, curve C, IP20, Thermal-magnetic, Suitable for isolation, Contact position indicator, Type of control: Handle, Local signaling: Trip indicator, Mounting mode: Fixed, Mounting bracket: DIN rail, Earth leakage protection: Independent block, 85x54x78.5mm, 0.375kg, White. Breaking capacity: 6 kA Icu in accordance with IEC 60947-2, 440 V AC 50/60 Hz, 20 kA Icu in accordance with EN 60947-2, 220...240 V AC 50/60 Hz, 10 kA Icu in according to EN 60947-2, 380...415 V AC 50/60 Hz, 36 kA Icu according to IEC 60947-2, 12...133 V AC 50/60 Hz, 20 kA Icu according to IEC 60947 -2, 220...240 V AC 50/60 Hz, 6000 A Icn according to EN 60898-1, 400 V AC 50/60 Hz, 6 kA Icu according to EN 60947-2, 440 V AC 50/60 Hz, 10 kA Icu according to EN 60947-2, 125...180 V DC, 36 kA Icu according to EN 60947-2, 12...133 V AC 50/60 Hz, 10 kA Icu according with IEC 60947-2, 380...415 V AC 50/60 Hz, 6000 A Icn according to IEC 60898-1, 400 V AC 50/60 Hz, 10 kA Icu according to IEC 60947-2, 125. ..180 V DC, utilization category: category A in accordance with IEC 60947-2, category A in accordance with EN 60947-2, suitable for isolating: yes in accordance with EN 60947-2, yes in accordance with IEC 60947- 2, yes according to IEC 60898-1, yes according to EN 60898-1, standards: EN 60947-2, EN 60 898-1, IEC 60947-2, IEC 60898-1.

View product online

Specifications

Rated current (A)	6
Curve	C
EAN	3606480093302
Manufacturer	Schneider
No. of poles	3P
Weight (kg)	0,375

This document is based on the product page published in our store and is provided for information only. It is not contractual. It

may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 28 November 2026