

Product sheet

Automatic circuit breaker iC60N 2P 10A curve-D

Brand: SCHNEIDER

Reference: IMPO A9F75210



iC60N Acti 9 thermal-magnetic circuit breaker, 2P, 10A, curve D, 50/60 Hz, IP20, thermal-magnetic, suitable for isolation, contact position indicator, handle control, trip indicator, fixed mounting, DIN rail support, protection against earth leakage with independent block, measures 85x36x78.5mm, weighs 0.25kg and is white. Breaking capacity: 10 kA Icu according to IEC 60947-2, 220...240 V AC 50/60 Hz, 36 kA Icu according to IEC 60947-2, 12...60 V AC 50/60 Hz, 36 kA Icu according to EN 60947-2, 12...60 V AC 50/60 Hz, 6000 A Icn according to EN 60898-1, 230 V AC 50/60 Hz, 20 kA Icu according to IEC 60947 -2, 100...133 V AC 50/60 Hz, 10 kA Icu conforming to EN 60947-2, 220...240 V AC 50/60 Hz, 20 kA Icu conforming to EN 60947-2, 100 ...133 V AC 50/60 Hz, 6000 A Icn conforming to IEC 60898-1, 230 V AC 50/60 Hz, utilization category A conforming to EN 60947-2 and IEC 60947-2, suitable for isolating according to IEC 60898-1, IEC 60947-2, EN 60898-1 and EN 60947-2, standards: EN 60947-2, IEC 60947-2, EN 60898-1 and IEC 60898-1.

[View product online](#)

Specifications

Rated current (A)	10
Curve	D
EAN	3606480080944
Manufacturer	Schneider
No. of poles	2P
Reference	SCHNEIDER A9F75210

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 17 September 2026