Product sheet



Automatic circuit breaker iC60N 2P 25A curve-D

Brand: SCHNEIDER

Reference: IMPO A9F75225

iC60N Acti 9 thermal-magnetic circuit breaker, 2P, 25A, curve D, 50/60 Hz, IP20, Thermal-magnetic, Suitable for sectioning, Contact position indicator, Type of control: Toggle, Local signaling: Trip indicator, Mode Mounting Bracket: Fixed, Mounting Bracket: DIN Rail, Earth Leakage Protection: Freestanding Block, 85x36x78.5mm, 0.25kg, White. Breaking capacity: 20 kA Icu according to EN 60947-2, 220...240 V AC 50/60 Hz, 10 kA Icu according to EN 60947-2, 72...125 V DC, 6 kA Icu of according to EN 60947-2, 440 V AC 50/60 Hz, 10 kA Icu according to IEC 60947-2, 72...125 V DC, 10 kA Icu according to EN 60947-2, 380...415 V AC 50/60 Hz, 20 kA Icu conforming to IEC 60947-2, 220...240 V AC 50/60 Hz, 36 kA Icu conforming to IEC 60947-2, 12...133 V AC 50/60 Hz, 6 kA Icu according to IEC 60947-2, 440 V AC 50/60 Hz, 6000 A Icn according to IEC 60898-1, 400 V AC 50/60 Hz, 36 kA Icu according to EN 60947- 2, 12...133 V AC 50/60 Hz, 10 kA Icu conforming to IEC 60947-2, 380...415 V AC 50/60 Hz, 6000 A Icn conforming to EN 60898-1, 400 V AC 50/60 Hz, utilization category: category A according to IEC 60947-2, category A according to EN 60947-2, suitable for isolating: yes according to EN 60947-2, yes according to IEC 60947- 2, yes according to EN 60898-1, yes according to IEC 60898-1, standards: EN 60898-1, IEC 609 47-2, IEC60898-1, EN60947-2.

View product online

Specifications

Rated current (A)	25
Curve	D
EAN	3606480080982
Manufacturer	Schneider
No. of poles	2P
Reference	SCHNEIDER A9F75225
Cable cross-section (mm²)	85x36

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 24 November 2026