

Product sheet

## Automatic circuit breaker iC60N 2P 32A curve-D

Brand: SCHNEIDER

Reference: IMPO A9F75232



iC60N Acti 9 thermal-magnetic circuit breaker, 2P, 32A, curve D, 50/60 Hz, IP20, Thermal-magnetic, Suitable for sectioning, Contact position indicator, Type of control: Toggle, Local signaling: Trip indicator, Mode Mounting Bracket: Fixed, Mounting Bracket: DIN Rail, Earth Leakage Protection: Freestanding Block, 85x36x78.5mm, 0.25kg, White. Breaking capacity: 10 kA Icu according to EN 60947-2, 72...125 V DC, 20 kA Icu according to IEC 60947-2, 220...240 V AC 50/60 Hz, 6 kA Icu according to according to IEC 60947-2, 440 V AC 50/60 Hz, 10 kA Icu according to EN 60947-2, 380...415 V AC 50/60 Hz, 6000 A Icn according to EN 60898-1, 400 V AC 50/60 Hz, 10 kA Icu conforming to IEC 60947-2, 380...415 V AC 50/60 Hz, 10 kA Icu conforming to IEC 60947-2, 72...125 V DC, 20 kA Icu conforming to EN 60947-2, 220...240 V AC 50/60 Hz, 6000 A Icn conforming to IEC 60898-1, 400 V AC 50/60 Hz, 36 kA Icu conforming to IEC 60947- 2, 12...133 V AC 50/60 Hz, 6 kA Icu conforming to EN 60947-2, 440 V AC 50/60 Hz, 36 kA Icu conforming to EN 60947-2, 12...133 V AC 50/60 Hz, utilization category: category A according to EN 60947-2, category A according to IEC 60947-2, suitable for isolating: yes according to EN 60898-1, yes according to IEC 60947- 2, yes according to IEC 60898-1, yes according to EN 60947-2, standards: IEC 60898-1, IEC 60 947-2, EN 60947-2, EN 60898-1.

[View product online](#)

### Specifications

|                   |                    |
|-------------------|--------------------|
| Rated current (A) | 32                 |
| Curve             | D                  |
| EAN               | 3606480080999      |
| Manufacturer      | Schneider          |
| No. of poles      | 2P                 |
| Reference         | SCHNEIDER A9F75232 |

If you have any questions, contact our support team

Item downloaded on 15 September 2026