

## Product sheet

# RCD VIGI IC60 3P 63A 300mA class CA

Brand: SCHNEIDER

Reference: IMPO A9V14363



Vigi iC60 differential block, 3P, 63A, 300mA, AC class, 50/60 Hz, IP20, instantaneous earth leakage protection delay, 7 steps of 9mm, without protection against overvoltage and with trip indicator. Adjustable clip mounting and DIN rail support. Electrical connection to MCB by screws. Comb busbar distribution block compatibility. Bare cable length 14mm (bottom). Rated operating voltage: 400 V AC 50/60 Hz according to EN 61009-1, 400/415 V AC 50/60 Hz according to IEC 61009-1, standards: IEC 61009-1, EN 61009-1. Measurements: 91x117x73.5mm. With a weight of 0.21kg and white.

[View product online](#)

## Specifications

|                     |                    |
|---------------------|--------------------|
| Frequency           | 50/60 Hz           |
| Rated current (A)   | 63                 |
| Sensitivity         | 300 mA             |
| Curve               | C                  |
| EAN                 | 3606480374753      |
| Manufacturer        | Schneider          |
| No. of poles        | 3P                 |
| Reference           | SCHNEIDER A9V14363 |
| Nominal voltage (V) | 380V               |

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 14 September 2026