

Product sheet

Electronic plant timer 400W 230V regulator

Brand: DINUY

Reference: DINUY MI PLA 001R



- Electronic timer for installation in mechanism box.
- 2-wire connection, does not need the Neutral.
- Valid for incandescent and halogen. It does not support LEDs, Low Consumption, Fluorescence, Extractors, etc.
- Activation by means of conventional non-luminous pushbuttons.
- It has 2 operating modes: Resettable timer or timed remote switch.

[View product online](#)

Description

Product reference MI PLA 001R
Supply Voltage (V) 230VAC
Frequency (Hz) 50
Own Consumption 5VA
LED Lamps (W) 0
Incandescent and Halogen 230V (W) 400
Halogen 12V with electronic transformer (W) 400
Halogen with ferromagnetic transformer (W) 320
Fluorescent Lamps (W) 0
Fluorescent Lamps (VA) 0
Contactor allowed No
Zero crossing No
2-wire installation
Permanent lighting No
Shutdown warning No
Minimum time delay (seconds) 30
Maximum timing (minutes) 10
Timed remote control YES
Lighted pushbuttons YES (Maximum 3 Units)

Operating Temperature (°C) (min) 0
Operating Temperature (°C) (max) 40
Permanent Luminous LED No
Mounting Mechanism box
Environmental Protection IP20 according to UNE20324
In accordance with UNE-EN60669-2-1 and UNE -EN60669-2-3

Specifications

EAN	8422447011296
Manufacturer	Dinuy
Nominal voltage (V)	230V

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 12 September 2026