

Product sheet

DALI dimmer regulator 1 channel

Brand: DINUY

Reference: DINUY RE KNT DA1



- DALI Dimming Actuator with 3 Broadcast output channels.
- Supports up to 64 DALI Ballasts or Drivers per channel (128 in total).
- Unidirectional Communication and Broadcast with the luminaires.
- Incorporates overload and short-circuit protection.
- Modular format (5 modules wide), DIN rail installation.
- It has a potentiometer for manual control, without the need for the Bus, which allows checking the perfect operation of the dimmer with the lamps.
- Anti-panic input for security systems.
- Programming by ETS: ETS4 program or later versions

[View product online](#)

Description

Product reference RE KNT DA1
Supply Voltage (V) 110VAC - 230VAC
Frequency (Hz) 50
Own Consumption 10W
Output Channels 3
Type of Load Ballast or DALI Driver
Maximum number of devices 128
DIN Rail Installation
No. of Modules 5
KNX Bus Control
Programming through ETS4 or later
Compatible with KNX
Type of connection terminals Captive screws
Cable section (mm²) 6
Storage temperature (°C) (min) -30

Storage temperature (°C) (max) 70
Operating Temperature (°C) (min) -5
Operating Temperature (°C) (max) 45
Environmental Protection IP20 according to UNE 20324
According to the Safety Directives 2014/35/EU; EMC 2014/30/EU
According to the KNX Standard 2.0//EN60669-1, 2-1 and 2-3

Specifications

EAN	8422447013993
Manufacturer	Dinuy

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 15 September 2026