

Product sheet

Differential switch DX3 2/40/30AC

Brand: LEGRAND

Reference: LEGRAND 411505



The DX3 2/40/30AC differential is a bipolar differential switch with a sensitivity of 30 mA and a capacity of 40A. It complies with the UNE EN 61008-1 standard and is of the AC type, which allows it to detect alternating component defects in electrical circuits.

Technical characteristics:

- Type: differential DX3-ID
- Poles: bipolar
- Nominal voltage: 230 V~
- Sensitivity: 30 mA
- Nominal current: 40A
- Number of modules: 2
- Complies with the UNE EN 61008-1 standard
- Type AC: detects alternating component defects
- Type A: detects faults in AC and DC components (specialized circuits: cookers, hobs, washing machines, etc.)
- Type Hpi: detects faults in AC and DC components (type A) with increased immunity to untimely trips (disturbed environments: computer circuits, lightning strikes, fluorescent lamps, etc.)
- Type B: detects faults in AC and DC components and DC faults without corrugation (machinery with variation speed control, photovoltaic installations, call centers, medical equipment, etc.)
- Suitable for auxiliaries, motorized controls and DX³ connection modules (except Type B)
- Screw/screw: upper entry and lower exit through screw terminals.

[View product online](#)

Specifications

High	77,8
Width	35,6
Sensitivity	30 mA
Curve	C
EAN	3245064115056
Manufacturer	Legrand
Intensity	40
# Elements	2
No. of poles	2P
Weight (kg)	0,21
Protection	IP20
Nominal voltage (V)	230V

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 28 September 2026