

Product sheet

Circuit breaker TX3 6kA-C 2P 32A

Brand: LEGRAND

Reference: LEGRAND 403609



The TX3 6KA-C circuit breaker is a two-pole 32A circuit breaker, which complies with the UNE EN-60898-1 standard and is designed for use in low voltage electrical installations.

Technical characteristics:

- 230/400 V~ bipolar magnetothermic automatic switch.
- Tripping curve C.
- Cutting power of 6000A.
- Connection with terminals protected against direct contact (IP20).
- Captive screws for easy installation.
- Incorporated label holder for easy identification.
- Terminalization capacity of up to 25 mm² flexible and 35 mm² rigid.
- They can be equipped with motorized controls and DX³ control and signaling auxiliaries.
- Automatic switches of the TX³ series available for nominal currents from 6A to 40A.

[View product online](#)

Specifications

High	77,8
Rated current (A)	32
Width	35,4
Curve	C
EAN	3245064036092
Manufacturer	Legrand
Intensity	32
# Elements	2
No. of poles	2P
Weight (kg)	0
Protection	IP20

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 24 October 2026