

Product sheet

Panel LED recessed 40W 4000K white 60x60cm

Brand: CRISTALRECORD

Reference: CR 30-125-40-400



The **40W 4350Lm 4000K LED Panel** is the perfect choice for illuminating offices and contract spaces. This square LED panel features a sleek and efficient design that provides high-quality neutral white light. Equipped with a high-quality LIFUD driver, this panel offers efficient performance and low power consumption. With an intensity of 4350 lumens, this panel is a brilliant choice for a variety of applications.

[View product online](#)

Description

The **40W 4350Lm 4000K LED Panel** is a versatile and efficient ceiling lighting solution that is ideal for a variety of environments, including offices and contract spaces. This square LED panel offers bright, uniform illumination that improves visibility and creates a comfortable work environment.

Stylish Square Design

- This LED panel features a square design with a white aluminum frame that provides it with a sleek and modern look. It fits perfectly into recessed ceilings with dimensions of 580x580mm.

Efficient LED Lighting

- Equipped with a high-performance LED lighting source, efficiency, this panel offers reduced energy consumption without compromising light quality. With a power of 40W, it provides an intensity of 4350 lumens.

High Quality LIFUD Driver

- The panel is equipped with a high quality LIFUD driver that ensures efficient performance and long lifespan. This driver contributes to the stability and reliability of the panel.

Neutral Color Temperature

- The 4000K color temperature creates a neutral white light that is suitable for a wide variety of applications. Provides bright, crisp lighting that is ideal for work environments.

Recessed Installation

- This panel installs recessed in the ceiling, making it perfect for spaces where clean, discreet lighting is needed. The square design easily integrates into the interior architecture.

The **40W 4350Lm 4000K LED Panel** is a high-quality lighting solution that combines energy efficiency with a design elegant. Whether in an office, meeting room or any other commercial environment, this LED panel provides efficient and uniform lighting that improves productivity and visual comfort

Specifications

Appliance class	Class II
Frequency	50hz
Opening angle	120
Colour	White
Cri (Ra)	80
Diameter embedment (mm)	580x580mm
EAN	8435197481448
Turned on (ON/OFF)	10000
Manufacturer	Cristalrecord
Lumens (lm)	4350
Battery included	No
Colour temperature	4000
Estimated life (h)	30000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 6 October 2026