

Product sheet

Panel LED Luena recessed 60W 4200K white 119.5x59.5cm

Brand: GSC

Reference: GSC 203400022



The **Luena 60W Recessed LED Panel** in white offers high-quality, energy-efficient lighting for any space. With a daylight of 4200K, this panel provides a clear and productive atmosphere, ideal for offices, kitchens, bathrooms and commercial areas. Its recessed design and white finish integrates perfectly into any modern decoration.

- **Power of 60W** with a luminous flux of **6000Lm** with diffuser and **6600Lm** without diffuser.
- Opening angle of **120°** for uniform light distribution.
- **Temperature color of 4200K**, offering balanced daylight.
- **Lifespan of 30,000 hours**, minimizing maintenance and replacements.
- Manufactured in **aluminum + PS**, guaranteeing durability and resistance

[View product online](#)

Description

The **Luena 60W Recessed LED Panel** redefines lighting with its power and versatility. Designed to meet lighting needs in a variety of environments, this LED panel combines functionality with style. It offers powerful and clear light, with a color temperature of 4200K that simulates daylight, creating more lively and energetic environments.

Its ability to be installed recessed makes it a discreet and elegant option to modernize any space. The possibility of adjusting the light intensity depending on whether it is used with or without a diffuser adds flexibility to its application, allowing the lighting level to be customized according to the needs of the area to be illuminated.

Highlighted features:

- **Wide opening angle of 120º**, guaranteeing wide and homogeneous light coverage.
- **Working temperature from -20ºC to +50ºC** , suitable for a wide range of environmental conditions.
- **UGR >22** and **SDCM <6**, ensuring quality lighting without glare or variations of color.
- **Instant start** with **100% immediate light**, ideal for areas that require instant lighting.
- **CRI (Ra) ≥80**, providing accurate and natural color representation.
- **Power factor (PF) of 0.95**, reflecting high efficiency in the use of energy.
- **100,000 On/Off cycles**, offering a long useful life and sustainability.
- **IP20 and IK05 protection**, designed for interiors with resistance to minor impacts.

Specifications

Opening angle	120
Colour	White
EAN	8433373076259
Material	AL - PS
Measures	119,5x59,5cm
Weight (kg)	3,55
Battery included	No
Protection	IP20
Nominal voltage (V)	230V
Estimated life (h)	30000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 7 October 2026