Product sheet



Panel LED Luena recessed 60W 6000K white 119.5x59.5cm

Brand: GSC

Reference: GSC 203400023

The **Luena 60W Recessed LED Panel** offers an advanced and versatile lighting solution for any interior space. With a cold light of 6000K and an impressive luminous flux, this panel is ideal for environments that require maximum clarity and energy efficiency. Thanks to its multiple installation options, it adapts to any need, whether recessed, suspended or as a surface.

- **Power of 60W** with a luminous flux of **6000Lm** with diffuser and **6600Lm** without diffuser.
- Opening angle of **120º** for wide and uniform light coverage. li>
- Color temperature of **6000K**, offering a **cool light** that improves concentration and clarity.
- Lifespan of **30,000 hours**, guaranteeing long-lasting and reliable lighting.
- Made of **aluminum + PS**, combining resistance with elegant design.

View product online

Description

Introducing the **Luena Recessed LED Panel**, a 60W lighting solution that redefines efficiency and style in LED lighting. This panel not only provides powerful lighting of **6000Lm** with diffuser and **6600Lm** without diffuser, but also offers the flexibility to adjust to different environments thanks to its varied installation options.

Designed to replace traditional panels, the Luena stands out for its cold light of **6000K**, perfect for creating stimulating and productive environments. Its wide opening angle of **120º** ensures extensive and uniform light distribution, ideal for offices, commercial areas, and residential spaces that seek to maximize clarity.

Among its most features Highlights include:

- **Working temperature from -20ºC to +50ºC**, which makes it suitable for a wide range of environmental conditions.
- **UGR >22** and **SDCM <6**, ensuring high quality lighting with minimal distraction from glare.
- **Instant start (<0.5s)** with **100% immediate light**, for visual comfort from the moment it is turned on.
- **CRI (Ra) ≥80**, ensuring natural and accurate color representation.
- **Power factor (PF) of 0.95**, reflecting its high energy efficiency.
- **No mercury (Hg 0.0)** and with a cycle of **100,000 On/Off**, highlighting its commitment to sustainability.
- **IP20 and IK05 protection** , offering durability and resistance within interiors

Specifications

Opening angle	120
Colour	White
EAN	8433373076266
Material	AL + PS
Measures	119,5x59,5cm
Weight (kg)	3,55
Battery included	No
Protection	IP20
Nominal voltage (V)	230V
Colour temperature	6500
Estimated life (h)	30000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 28 November 2026