

Product sheet

Panel LED Gilé recessed 40W 3000-6000K white 59.5x59.5cm

Brand: GSC

Reference: GSC 203400026



The **Gilé Recessed LED Panel** of 40W in white is a modern and efficient lighting solution that adapts to any environment, offering versatile installation options such as downlight, suspended or surface-mounted. With a wide range of color temperatures, from warm light to cold light, this panel is perfect for creating the desired atmosphere in any space.

- **40W power** with a luminous flux of **3600Lm** with diffuser and **4400Lm** without diffuser.
- Wide opening angle of **120°** for coverage of uniform light.
- Color temperature options: **3000K (warm light)**, **4000K (daylight)**, **6000K (cold light)**.
- Lifespan exceptional **50,000 hours**, reducing the need for maintenance.
- Design in **aluminum + PS**, combining durability with modern aesthetics.

[View product online](#)

Description

The **Gilé Recessed LED Panel** represents the latest technology in LED lighting, offering an elegant and efficient solution for all types of spaces. With a power of 40W, this panel provides powerful and uniform lighting, capable of adapting to the specific needs of each user thanks to its varied color temperature options.

Its recessed design offers a clean and modern, while the possibility of installation in different modalities makes it extremely versatile. Whether as a downlight for focused lighting, suspended to add a contemporary touch, or surface mounted for those spaces without a false ceiling, the Gilé Panel adjusts to your preferences.

Highlighted features:

- **Optimized dimensions** for easy installation in various environments.
- **Power/Lumens:** Adjustable lighting capacity depending on the installation with or without diffuser.
- **Working temperature from -20°C to +50°C**, guaranteeing optimal performance under various conditions.
- **UGR >19** and **SDCM <6**, ensuring superior light quality without glare.
- **Instant start (<0.5s)** with **100% immediate light**, for instant comfort.
- **CRI (Ra) ≥80**, for realistic and vibrant color representation.
- **Power factor (PF) of 0.95**, improved energy efficiency.
- **No mercury (Hg 0.0)** and **100,000 On cycles/Off**, environmentally friendly and long lasting.
- **IP20 and IK05**, for safe indoor use and impact resistance.

Specifications

Opening angle	120
Colour	White
EAN	8433373076471
Material	AL - PS
Measures	595x595x30mm
Weight (kg)	1,911
Battery included	No
Protection	IP20
Colour temperature	4000
Estimated life (h)	50000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 1 October 2026