

Product sheet

Panel LED Borma surface 40W 4200K black 60x60cm

Brand: GSC

Reference: GSC 203405025



The **Borma 40W Surface LED Panel** in black offers an elegant, high-performance lighting solution for any space. Ideal for environments that require simple installation without drilling in the ceiling, this panel provides 4200K daylight with a wide opening angle and notable luminous efficiency. Its aluminum and PS design makes it a durable and aesthetically attractive option.

- **Power of 40W** with a luminous flux of **4200Lm** with diffuser and **4650Lm** without diffuser.
- Opening angle of **120°** for extensive and uniform light coverage.
- Temperature color of **4200K**, creating an ideal daylight environment for multiple applications.
- **Lifespan of 30,000 hours**, ensuring long-term illumination with minimal maintenance.
- Contemporary design in **black**, perfect to complement any modern decoration.

[View product online](#)

Description

The **Borma Surface LED Panel** redefines interior lighting with its advanced LED technology and practical surface installation. With an effective power of 40W, this panel is not only energy efficient but also offers excellent lighting performance, both with a diffuser (4200Lm) and without a diffuser (4650Lm), adapting perfectly to the lighting needs of any environment.

Its elegant and minimalist design in black integrates perfectly into any space, from modern offices to residential interiors, without the need to drill holes for installation. This makes it ideal for places where you want to avoid alterations to the ceiling or are simply looking for a flexible and easy-to-assemble lighting solution.

Highlights:

- **Working temperature from -20°C to +50°C**, making it suitable for a wide range of environments.
- **UGR of 22** and **SDCM lower to 6**, ensuring comfortable, high-quality lighting without glare.
- **Instant on (<0.5s)** with **100% immediate light**, providing comfort and efficiency from the first moment.
- **CRI (Ra) of ≥80**, for accurate and vibrant color reproduction.
- **Power factor (PF) of 0.95**, maximizing the energy efficiency of the panel.
- **Free of mercury (Hg 0.0)** and with **100,000 On/Off cycles**, highlighting its durability and sustainability.
- **IP20 and IK05 classification**, guaranteeing protection and resistance in indoor environments

Specifications

Opening angle	120
Colour	Black
EAN	8433373076358
Material	AL + PS
Weight (kg)	1,804
Battery included	No
Protection	IP20
Nominal voltage (V)	230V

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 8 October 2026