

Product sheet

Panel LED Kisongo surface 36W 4200K black 90x30cm

Brand: GSC

Reference: GSC 203405029



The **Kisongo 36W LED Panel** in black finish combines contemporary design with advanced functionality to illuminate spaces with **3600Lm**. Offering a **daylight** of **4200K**, this panel ensures homogeneous and comfortable lighting, ideal for any environment. Its surface installation makes it perfect for environments where it is not desired or cannot be recessed, simplifying the renovation of spaces with style and efficiency.

- **High Luminosity:** 3600Lm with diffuser, 3900Lm without diffuser, for powerful and uniform lighting.
- **Optimal Color Temperature:** 4200K, providing natural light during the day.
- **Superior Durability:** 30,000 hours of useful life with a robust IP20 and IK05 design.
- **Energy Efficient:** With a power factor of 0.95, maximizes the energy use.
- **Easy Installation:** Surface mounting for simple integration without the need for works.

[View product online](#)

Description

The **Kisongo LED Panel** of **36W** in black is a superior lighting solution for those who value both aesthetics and functionality. This panel is not only efficient in terms of energy and luminosity but also in its installation and maintenance. With a wide opening angle of **120°**, it illuminates large areas evenly, while its color temperature of **4200K** simulates natural daylight, ideal for residential and commercial applications. commercial.

- **Versatility of Application:** Its elegant black finish and modern design complement any decoration.

- **High Color Rendering:** CRI (Ra) ≥80 for natural and vivid color reproduction.
- **Instant Start:** Less than 0.5 seconds to reach 100% brightness, no waiting.
- **Resistance and Safety:** IP20 and IK05 ratings for durability and protection in indoor environments.
- **Ecological and Safe:** Mercury-free (Hg 0.0) and with low energy consumption, it is environmentally friendly.

Specifications

Opening angle	120
Colour	Black
Cri (Ra)	80
EAN	8433373076396
Material	Aluminio
Weight (kg)	1,773
Battery included	No
Protection	IP20
Nominal voltage (V)	230V
Type of installation	Surface

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 15 September 2026