

Product sheet

Surface-mounted electrical panel PRISMASET XS 18 modules 3 rows white

Brand: SCHNEIDER

Reference: SCHNEIDER LVSXL318



This **PrismaSeT XS modular enclosure** is designed for surface installations, with a capacity of 3 rows of 18 modules. Made of high-quality technoplastic, its ergonomic and flexible design simplifies wiring and maintenance

[View product online](#)

Description

It is designed to offer **maximum flexibility** and optimal ergonomics for surface-mounted installations. Cable access is optimized with removable entry plates located at the top and bottom, facilitating the use of cables, tubes, or ducts. Its technoplastic construction ensures heat resistance (650 °C) and durability.

It complies with all necessary standards to guarantee safety and performance.

It includes the following components for immediate and efficient installation:

- **Dimensions:** 426 x 600 x 145 mm (width x height x depth).
- **Capacity:** 3 rows for a total of 54 modules of 18 mm.
- **Terminals:** Ground block with 28 outputs (6x25 mm² + 22x4 mm²).
- **Operating temperature:** -25 °C to 60 °C.
- **Material:** White technoplastic RAL 9003, highly resistant.
- **Electrical insulation class:** Class II.
- **Standards:** IEC 60670-1/24, IEC 61439-1/3

Specifications

High	60
Rated current (A)	125
Width	42.6
Colour	White

EAN	8499213131298
Manufacturer	Schneider
Material	Termoplástico
Measures	426 x 600 x 145 mm
Rated voltage	400V
Type of installation	Surface

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 5 October 2026