Product sheet

Twilight switch Orbis Vega OB131712

Brand: ORBIS

Reference: ORBIS OB131712



Installation: surface, wall as on your own staff.

Simple contact with potential of 5 to 300 lux.

View product online

Description

Twilight switch surface and with external adjustment.

High degree of protection IP 54, which allows you to work in extreme conditions.

Delay of activation to avoid turned on or off unwanted.

LED operation indicator.

Mounting surface wall.

Supply voltage:230 V ac (±10%), 50 Hz

Power break:10 A 250 V ac

Sensitivity:5-300 lux

Delay of action:60 seconds

Operating temperature:-30 ºC to +50 ºC

Degree of protection:IP 54 according to en 60529

Maximum loads

Incandescent lamps:2000 W
Fluorescent:100 VA
Halogen low-voltage:1000 VA
Halogens (230V AC):1000 W
Lamps low power consumption:100 VA
Lamps leds:50 VA

Specifications

EAN	8426709100872
Manufacturer	Orbis
Protection	IP54
Nominal voltage (V)	230V
Type of installation	Surface

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 5 November 2026