

Product sheet



KUKKO 3-LEG extractor with depth stop and dimensions 160 x 150 mm.

Brand: Kukko

Reference: TUR 30-2

The Kukko-30-2 is a 3-leg puller, ideal for indoor and outdoor applications. Its robust design allows for the removal of asymmetrical parts, and its depth stop prevents slippage. It includes a grease tube to keep the spindle lubricated.

[View product online](#)

Description

The **Kukko-30-2-3-Legged Extractor Series 30-Classic** is a universal extraction tool designed to offer exceptional performance in a variety of applications. Measuring **160 x 150 mm**, this extractor stands out for its robustness and reliability, characteristics that have established the KUKKO brand worldwide. Its original design allows for versatile use, as it can be used as both an external and internal extractor simply by rotating the extraction hooks. Furthermore, it is suitable for extracting asymmetrical machined parts, making it an indispensable tool in any workshop.

The extractor features a depth stop on the spindle head that prevents the wrench from slipping, ensuring safe operation. Its crossbar, designed up to size -30, includes a hexagonal head that provides a better grip. The puller's legs remain constantly parallel, ensuring that only the support surfaces come into contact with the part being pulled, allowing for concentric extraction and optimal grip.

- Universal 3-leg pullers.
- Original KUKKO design, robust and reliable.
- Parallel legs in every position.
- Even force distribution.
- Robust finish and high performance.
- Universal application with interchangeable legs.
- Use as outdoor or indoor pullers.
- Includes a tube of special Kukko grease.
- Maximum stability in the sliding part of the leg.
- Optimized geometry for easy movement and fixing.

Specifications

High	4,70
Width	25,00
EAN	4021176013478
Manufacturer	Kukko
Weight (kg)	3,5000
Depth	25,00

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 28 October 2026