

Product sheet

RUKO HSS Conical Drill Bit with Stop and Diameter 3.0-10.2mm

Brand: Ruko

Reference: TUR 101042



Ruko-101042 HSS tapered drill bit with stop, 3.0 to 10.2 mm diameter. Optimized design for precise cutting of non-ferrous metals, steel, and plastics. Includes translucent plastic case. Ideal for sheet metal up to 4 mm thick.

[View product online](#)

Description

The Ruko-101042 tapered drill bit is designed to deliver exceptional performance in a wide variety of materials. Featuring a split point cutting edge according to DIN 1412 C, this drill bit has a 118° cutting angle and a 20/30° taper angle, enabling efficient and precise cutting. Its right-hand cutting design, combined with CBN grinding, ensures a smooth drilling process, minimizing noise, vibration, and burr formation. This tool is ideal for working with non-ferrous metals, steel, thermoplastics, and hard plastics, as well as sheet metal up to 4 mm thick. Furthermore, it comes in a translucent plastic case for easy storage and transport.

- **Cutting point:** Split point DIN 1412 C
- **Cutting angle:** 118°
- **Cone angle:** 20/30°
- **Cutting direction:** Right-hand
- **Grinding:** CBN for optimal cutting
- **Flute design:** Efficient chip evacuation
- **Compatible materials:** Non-ferrous metals, steel, thermoplastics, and hard plastics
- **Maximum sheet thickness:** 4 mm
- **Packaging:** Translucent plastic case with hanger

Specifications

High	1,52
Width	1,52
EAN	4007140001283
Manufacturer	Ruko
Weight (kg)	0,0200

Depth	6,20
-------	------

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 22 October 2026