

Product sheet

RUKO HSS Cone Drill Bit with Stop and Diameter 3.0-11.8mm

Brand: Ruko

Reference: TUR 101043



Ruko-101043 HSS tapered drill bit with stop, 3.0 to 11.8 mm diameter. Designed for precise cutting of non-ferrous metals, steel, and plastics. Includes a translucent plastic case. Ideal for sheet metal up to 4 mm thick.

[View product online](#)

Description

The Ruko-101043 tapered drill bit is a high-precision tool designed to deliver exceptional performance in a variety of materials. Featuring a split point cutting edge according to DIN 1412 C, this drill bit has a 118° cutting angle and a 20/30° taper angle, allowing for easier and more efficient drilling starts. Its right-hand cutting design, combined with CBN grinding, ensures a clean and precise cut, minimizing noise, vibration, and burr formation during the drilling process.

This drill bit is suitable for working with non-ferrous metals, steel, thermoplastics, and hard plastics, as well as sheet metal up to 4 mm thick.

It comes in a translucent plastic case for easy storage and transport, and includes a hanger for convenient organization.

- Cutting point with split point DIN 1412 C
- Cutting angle: 118°
- Cone angle: 20/30°
- Right-hand cutting
- CBN grinding for optimal cutting
- Chip evacuation channel design
- Minimizes noise and vibration
- No burr formation
- Suitable for non-ferrous metals, steel, and hard plastics
- Translucent plastic case with hanger

Specifications

High	1,68
Width	1,68
EAN	4007140001290
Manufacturer	Ruko
Weight (kg)	0,0200
Depth	6,60

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 25 October 2026