

Product sheet

**RUKO HSS 90° conical
countersink Ø max. 28 mm DIN
335 form C**

Brand: Ruko

Reference: TUR 102133



Ruko-102133 Countersink, DIN 335 Form C, 90°, HSS. Maximum diameter 28 mm. Ideal for non-ferrous metals, steel, and hard plastics. Optimized design for efficient, vibration-free cutting. Includes translucent plastic case.

[View product online](#)**Description**

The Ruko-102133 tapered countersink is a high-precision tool designed to deliver exceptional performance when countersinking various materials. Featuring a split-point cutting edge according to DIN 1412 C, this countersink offers a 118° cutting angle and a 20/30° taper angle, enabling efficient and clean right-hand cutting. Its innovative design, including CBN grinding and optimized chip evacuation channels, ensures noise-, vibration-, and burr-free cutting, enhancing both user experience and surface finish quality.

This countersink is suitable for working with non-ferrous metals, steel, thermoplastics, and hard plastics, as well as sheet metal up to 4 mm thick.

Its 90° countersink angle and Morse taper handle ensure a firm grip and comfortable handling, while the three cutting edges provide greater efficiency in the countersinking process.

- Cutting point with split point DIN 1412 C
- Cutting angle: 118°
- Taper angle: 20/30°
- Right-hand cutting
- CBN ground for optimal cutting
- Chip flute design
- Suitable for non-ferrous metals, steel, and hard plastics
- Metal sheet capacity up to 4 mm thick
- Countersink angle: 90°
- Translucent plastic case with hanger

Specifications

High	3,30
Width	3,30
EAN	4007140003027
Manufacturer	Ruko
Weight (kg)	0,1900
Depth	12,20

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 17 September 2026