

Product sheet

RUKO manual countersink form C 90°, maximum diameter 16.5 mm, DIN 335.

Brand: Ruko

Reference: TUR 102145

Ruko-102145 manual countersink, C-shaped 90°, with a maximum diameter of 16.5 mm. Designed for precise cutting of non-ferrous metals, steel, and plastics. Includes a translucent plastic case. Ideal for sheet metal up to 4 mm thick.

[View product online](#)**Description**

The Ruko-102145 DIN 335 Form C 90° Manual Countersink is a high-precision tool designed to deliver efficient and clean cuts in a variety of materials. Featuring a cutting point incorporating DIN 1412 C split point technology, this countersink offers a 118° cutting angle and a 20/30° taper angle, enabling optimized right-hand cutting for diverse applications. Its innovative design, including CBN grinding and chip evacuation channels, ensures superior performance by minimizing noise, vibration, and burr formation during the cutting process.

This countersink is ideal for working with non-ferrous metals, steel, thermoplastics, and hard plastics, as well as sheet metal up to 4 mm thick.

Furthermore, it comes in a translucent plastic case that facilitates storage and transport, incorporating a hanger for added convenience.

- Cutting point with split point DIN 1412 C
- Cutting angle: 118°
- Cone angle: 20/30°
- Right-hand cutting
- CBN grinding for precise cutting
- Chip evacuation channel design
- Minimizes noise and vibration
- No burr formation
- Suitable for non-ferrous metals, steel, and hard plastics
- Translucent plastic case with hanger

Specifications

High	4,00
Width	4,00
EAN	4007140003164
Manufacturer	Ruko
Weight (kg)	0,0900
Depth	14,50

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 13 September 2026