

Product sheet

RUKO HSS solid drill bit with Weldon shank Ø 13 mm for high precision and durability.

Brand: Ruko

Reference: TUR 1081213



Solid 3S HSS drill bit with Weldon shank (Ø 13 mm) and 30 mm depth. Designed for pillar and floor drills, ideal for steel, light metals and non-ferrous metals. Includes translucent plastic case.

[View product online](#)**Description**

The Ruko-1081213 "Solid 3S" HSS Weldon Shank Drill Bit (Ø 13 mm) is a high-precision tool designed to deliver exceptional performance in drilling applications. With a drilling depth of 30 mm and a CBN grind that provides three cutting edges, this drill bit is ideal for magnetic base pillar drills and floor drills using Morse taper connections, and is compatible with adapters 108 302 and 108 303. Its design allows for direct connection to RUKO RS 10 type drills, facilitating its use in various configurations.

The "Solid 3S" drill bit stands out for its ability to advantageously replace hollow drill bits in small-diameter drills, making it a versatile and efficient option.

It is suitable for drilling steel beams and sheets, cast steel, as well as light and non-ferrous metals, guaranteeing high-quality results with every drill.

- Diameter: Ø 13 mm
- Drilling depth: 30 mm
- Material: HSS (High-Speed Steel)
- Grinding: CBN with 3 cutting edges
- Compatible with magnetic base pillar drills
- Use with adapters 108 302/108 303
- Direct connection to RUKO RS 10 type drills
- Ideal for steel beams and sheets
- Includes translucent plastic case with hanger
- Versatile for light and non-ferrous metals

Specifications

High	3,00
Width	3,00
EAN	4007140113450
Manufacturer	Ruko
Weight (kg)	0,0700
Depth	9,00

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 27 October 2026