Product sheet

RUKO HSS solid drill bit with Weldon shank Ø 14 mm for precise drilling.

Brand: Ruko

Reference: TUR 1081214

Solid 3S HSS drill bit with Weldon shank (Ø 14 mm) and 30 mm depth. Designed for pillar and floor drills, ideal for steel, light metals, and non-ferrous metals. Includes a translucent plastic storage case.

View product online

Description

The Ruko-1081214 "Solid 3S" HSS Weldon Shank Drill Bit (Ø 14 mm) is a high-precision tool designed to deliver exceptional performance in drilling applications. With a drilling depth of 30 mm and a CBN grind featuring three cutting edges, this drill bit is ideal for magnetic base pillar drills and bench drills using Morse taper connections, facilitating its use with adapters 108 302 and 108 303. Its design allows for direct connection to RUKO RS 10 type drills, ensuring efficient integration into your work equipment.

The "Solid 3S" stands out for its ability to advantageously replace hollow drill bits in small-diameter drills, making it a versatile and effective option.

It is suitable for drilling steel beams and sheets, cast steel, as well as light and non-ferrous metals, ensuring high-quality results in every application.

- Diameter: Ø 14 mm
- Drilling depth: 30 mm
- Material: HSS (High-Speed Steel)
- Grinding: CBN with 3 cutting edges
- Connection: Weldon shank
- Compatible with magnetic base pillar drills
- Use with adapters 108 302/108 303
- Direct connection to RUKO RS 10 type drills
- Ideal for steel, cast steel and non-ferrous metals
- Includes translucent plastic case with hanger

Specifications

High	3,00
Width	3,00
EAN	4007140113467
Manufacturer	Ruko
Weight (kg)	0,0700
Depth	9,00

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 15 October 2026