

Product sheet

**RUKO HSS hollow drill bit,
Weldon shank 30 mm depth,
diameter 36 mm.**

Brand: Ruko

Reference: TUR 108236

HSS hollow drill bit with Weldon shank, 30 mm depth and 36 mm diameter. Ideal for pillar and bench drills. Designed for drilling steel, light metals, and non-ferrous metals. Includes a translucent plastic case.

[View product online](#)**Description**

The Ruko-108236 hollow drill bit is a high-precision tool designed to deliver exceptional performance in industrial drilling applications. With a drilling depth of 30 mm and a diameter of 36 mm, this drill bit is manufactured with a polycrystalline cubic boron nitride (CBN) grinding process, ensuring high cutting power and a long service life. It is ideal for use on magnetic base pillar drills and floor drills with a Morse taper connection, using adapters 108 302 or 108 303. It also connects directly to RUKO RS 10 type drills, making it a versatile option for various applications.

- **Drilling depth:** 30 mm
- **Diameter:** 36 mm
- **Material:** CBN (polycrystalline cubic boron nitride)
- **Compatibility:** Magnetic base pillar drills and floor drills with Morse taper
- **Adapters required:** 108 302/108 303
- **Direct connection:** RUKO RS type drills 10
- **Applications:** Drilling of steel beams and sheets, cast steel, light and non-ferrous metals
- **Cutting power:** High performance
- **Durability:** Long service life
- **Packaging:** Translucent plastic case with hanger

Specifications

High	5,00
Width	5,00
EAN	4007140043870
Manufacturer	Ruko
Weight (kg)	0,1700

Depth	9,00
-------	------

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 7 October 2026