

Product sheet

HSS RUKO hollow drill bit, Weldon shank 55 mm depth, diameter 26 mm.

Brand: Ruko

Reference: TUR 108526

Ruko-108526 HSS hollow drill bit with Weldon shank and 55 mm depth (Ø 26 mm). Ideal for pillar and bench drills. Designed for drilling steel, light metals, and non-ferrous metals. Includes a translucent plastic case.

[View product online](#)

Description

The Ruko-108526 hollow drill bit is designed to deliver exceptional performance in industrial drilling applications. With a drilling depth of 55 mm and a diameter of 26 mm, this tool is ideal for magnetic base pillar drills and bench drills that use a Morse taper connection, via adapters 108 302 or 108 303. Its high-speed steel (HSS) construction and CBN grinding ensure high cutting power, allowing for easy drilling of steel beams and plates, cast steel, as well as light and non-ferrous metals. The drill bit is designed to provide a long service life, making it a reliable choice for professionals who require precision and durability in their projects.

- **Depth:** 55 mm
- **Diameter:** 26 mm
- **Material:** HSS (High-Speed Steel)
- **Grinding:** CBN
- **Compatibility:** Magnetic base pillar drills and Morse taper bench drills
- **Adapters:** 108 302/108 303
- **Applications:** Drilling steel beams and plates, cast steel, light and non-ferrous metals
- **Cutting power:** High performance
- **Life Useful:** Long-lasting
- **Presentation:** Translucent plastic case with hanger

Specifications

High	4,00
Width	4,00
EAN	4007140044105
Manufacturer	Ruko

Weight (kg)	0,1600
Depth	9,00

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 15 October 2026