

Product sheet

RUKO HSS hollow drill bit, Weldon shank, 55 mm deep (Ø 32 mm)

Brand: Ruko

Reference: TUR 108532

Ruko-108532 HSS hollow drill bit with Weldon shank, designed for pillar and floor drills. 55 mm depth and 32 mm diameter. Ideal for steel, light metals, and non-ferrous metals. Includes translucent plastic case.

[View product online](#)

Description

The Ruko-108532 hollow drill bit is designed to deliver exceptional performance in industrial drilling applications. With a drilling depth of 55 mm and a diameter of 32 mm, this tool is ideal for magnetic base pillar drills and bench drills with a Morse taper connection, using adapters 108 302 or 108 303. Its high-speed steel (HSS) construction and CBN grinding ensure high cutting power and a long service life, making it a reliable choice for drilling steel beams and plates, cast steel, light metals, and non-ferrous metals.

- **Drilling Depth:** 55 mm
- **Diameter:** 32 mm
- **Material:** HSS (High-Speed Steel)
- **Grinding:** CBN
- **Compatibility:** Magnetic base pillar drills and bench drills with Morse taper
- **Required adapters:** 108 302/108 303
- **Compatible models:** RUKO RS 20, RS 30
- **Applications:** Drilling of steel beams and sheets, cast steel, light and non-ferrous metals
- **Durability:** High cutting power and long service life
- **Packaging:** Translucent plastic case with hanger

Specifications

High	5,00
------	------

Width	5,00
EAN	4007140044167
Manufacturer	Ruko
Weight (kg)	0,1900
Depth	9,00

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 17 October 2026