

Product sheet

HSS RUKO hollow drill bit, Weldon shank 55 mm depth, diameter 37 mm.

Brand: Ruko

Reference: TUR 108537

Ruko-108537 HSS hollow drill bit with Weldon shank and 55 mm depth (Ø 37 mm). Ideal for pillar and bench drills. Designed for drilling steel, light metals, and non-ferrous metals. Includes a translucent plastic case.

[View product online](#)

Description

The Ruko-108537 HSS hollow drill bit is a high-precision tool designed to deliver exceptional performance in industrial drilling applications. With a depth of 55 mm and a diameter of 37 mm, this drill bit is ideal for magnetic base pillar drills and bench drills that use a Morse taper connection, and is compatible with adapters 108 302 and 108 303. Its design allows for efficient drilling of steel beams and sheets, cast steel, as well as light and non-ferrous metals, guaranteeing high cutting power and a long service life.

- **Depth:** 55 mm
- **Diameter:** 37 mm
- **Material:** HSS (High-Speed Steel)
- **Grinding:** CBN (Cubic Boron Nitride)
- **Compatibility:** Magnetic base pillar drills and bench drills with Morse taper
- **Adapters:** 108 302/108 303
- **Applications:** Drilling of steel beams and sheets, cast steel, light and non-ferrous metals
- **Cutting power:** High performance
- **Durability:** Long service life
- **Packaging:** Translucent plastic case with hanger

Specifications

High	5,00
------	------

Width	5,00
EAN	4007140044211
Manufacturer	Ruko
Weight (kg)	0,2100
Depth	9,00

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 30 September 2026