
Product sheet



RUKO 15mm diameter high precision HSS-G core drill bit.

Brand: Ruko

Reference: TUR 128015

The Ruko-128015 HSS-G (Ø 15 mm) core drill is ideal for alloy steels, non-ferrous metals, and plastics. With a material thickness of up to 2.5 mm and a cutting depth of 5 mm, it is resharpenable and requires minimal pressure.

View product online

Description

The Ruko-128015-HSS-G (Ø 15 mm) hole saw is a high-precision tool designed for drilling in a wide variety of materials. With a material thickness of up to 2.5 mm and a cutting depth of 5.0 mm, this hole saw is ideal for jobs requiring fine, controlled cuts. Its right-hand cutting design and resharpenable design ensure a long service life and consistent performance in demanding applications.

This tool is especially recommended for drilling alloy steels with hardnesses up to 800 N/mm², as well as cast steel, non-ferrous metals, light metals, plastics, reinforced fabrics, plasterboard, and in light construction. However, it is important to note that it is not suitable for hammer drilling.

For optimal use, it is recommended to apply light pressure when starting to drill, maintaining constant pressure and avoiding oscillating movements.

Additionally, the use of coolant is recommended to improve performance and extend tool life.

- Diameter: Ø 15 mm
- Material thickness: up to 2.5 mm
- Cutting depth: 5.0 mm
- Right-hand cutting
- Resharpenable
- Recommended for alloy steels (up to 800 N/mm²)
- Compatible with non-ferrous and light metals
- Use on plastics and reinforced fabrics
- Not suitable for hammer drilling

- Use of coolant recommended

Specifications

High	3,00
Width	3,00
EAN	4007140294708
Manufacturer	Ruko
Weight (kg)	0,0600
Depth	12,00

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 21 November 2026