
Product sheet



RUKO 30mm diameter high precision HSS-G core drill bit.

Brand: Ruko

Reference: TUR 128030

The Ruko-128030 HSS-G (Ø 30 mm) core drill is ideal for alloy steels, non-ferrous metals, and plastics. With a material thickness of up to 2.5 mm and a cutting depth of 5 mm, it is resharpenable and requires minimal pressure.

View product online

Description

The Ruko-128030-HSS-G (Ø 30 mm) hole saw is a high-precision tool designed for drilling in a wide variety of materials. With a material thickness of up to 2.5 mm and a cutting depth of 5.0 mm, this hole saw is ideal for working with alloy steels, cast steel, non-ferrous metals, light metals, plastics, reinforced fabrics, drywall, and in light construction. Its right-hand cutting design allows for optimal performance and increased durability, as it is resharpenable, extending its service life and reducing long-term costs.

It is important to note that this tool is not suitable for hammer drilling. It is recommended to apply light pressure when starting to drill and maintain constant pressure throughout the process.

For best results, it is suggested to avoid oscillating movements and use coolant to help maintain the proper temperature during use.

- Diameter: Ø 30 mm
- Material thickness: up to 2.5 mm
- Cutting depth: 5.0 mm
- Right-hand cutting
- Resharpenable
- Recommended for alloy steels (up to 800 N/mm² hardness)
- Compatible with cast steel and non-ferrous metals
- Ideal for plastics and reinforced fabrics
- Not suitable for hammer drilling
- Use of coolant recommended

Specifications

High	5,00
Width	5,00
EAN	4007140294852
Manufacturer	Ruko
Weight (kg)	0,1200
Depth	12,00

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 29 November 2026