
Product sheet



RUKO 31mm diameter high precision HSS-G core drill bit.

Brand: Ruko

Reference: TUR 128031

The Ruko-128031 HSS-G (Ø 31 mm) hole saw is ideal for alloy steels, non-ferrous metals, and plastics. With a material thickness of up to 2.5 mm and a cutting depth of 5 mm, it is resharpenable and requires minimal pressure.

View product online

Description

The Ruko-128031 HSS-G (Ø 31 mm) hole saw is a high-precision tool designed for drilling in a wide variety of materials. With a material thickness of up to 2.5 mm and a cutting depth of 5.0 mm, this hole saw is ideal for working with alloy steels, cast steel, non-ferrous metals, light metals, plastics, reinforced fabrics, drywall, and light construction materials. Its right-hand cutting design allows for efficient performance and a clean finish on every hole.

It is important to note that this tool is not suitable for hammer drilling. It is recommended to apply light pressure when starting to drill, maintaining constant pressure throughout the process.

For best results, it is suggested to avoid oscillating movements and use coolant to help extend the tool's lifespan.

- Diameter: Ø 31 mm
- Material thickness: up to 2.5 mm
- Cutting depth: 5.0 mm
- Right-hand cut
- Resharpenable
- Recommended for alloy steels (up to 800 N/mm² hardness)
- Compatible with cast steel and non-ferrous metals
- Ideal for plastics and reinforced fabrics
- Not suitable for hammer drilling
- Use of coolant recommended

Specifications

High	5,00
Width	5,00
EAN	4007140294869
Manufacturer	Ruko
Weight (kg)	0,1200
Depth	12,00

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 2 November 2026