

Product sheet

RUKO 32mm diameter high precision HSS-G core drill bit.

Brand: Ruko

Reference: TUR 128032

The Ruko-128032 HSS-G (Ø 32 mm) core drill is ideal for alloy steels, non-ferrous metals, and plastics. With a material thickness of up to 2.5 mm and a cutting depth of 5 mm, it is resharpenable and requires minimal pressure.

[View product online](#)

Description

The Ruko-128032-HSS-G (Ø 32 mm) hole saw is a high-precision tool designed for drilling in a wide variety of materials. With a material thickness of up to 2.5 mm and a cutting depth of 5.0 mm, this hole saw is ideal for jobs requiring fine, controlled cuts. Its right-hand cutting design allows for greater efficiency in the drilling process, while its resharpenable design ensures a long service life and consistent performance.

This tool is especially recommended for alloy steels with hardnesses up to 800 N/mm², as well as for cast steel, non-ferrous metals, light metals, plastics, reinforced fabrics, plasterboard, and light construction applications.

However, it is important to note that it is not suitable for hammer drilling.

- Diameter: Ø 32 mm
- Material thickness: up to 2.5 mm
- Cutting depth: 5.0 mm
- Right-hand cutting
- Resharpenable
- Recommended for alloy steels (up to 800 N/mm²)
- Suitable for non-ferrous and light metals
- Compatible with plastics and reinforced fabrics
- Not suitable for hammer drilling
- Requires low pressure to start drilling

For optimal performance, it is recommended to drill with low and constant pressure, avoiding oscillating movements and using coolant during the process.

Specifications

High	5,00
Width	5,00
EAN	4007140294876
Manufacturer	Ruko
Weight (kg)	0,1200
Depth	12,00

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 30 September 2026