


Product sheet

RUKO 33mm diameter high precision HSS-G core drill bit.

Brand: Ruko

Reference: TUR 128033

The Ruko-128033 HSS-G (Ø 33 mm) hole saw is ideal for alloy steels, non-ferrous metals, and plastics. With a material thickness of up to 2.5 mm and a cutting depth of 5 mm, it is resharpenable and requires minimal pressure.

[View product online](#)

Description

The Ruko-128033-HSS-G (Ø 33 mm) hole saw is a high-precision tool designed for drilling in a wide variety of materials. With a material thickness of up to 2.5 mm and a cutting depth of 5.0 mm, this hole saw offers a right-angle cut and is resharpenable, ensuring a long service life and consistent performance. It is especially recommended for working with alloy steels up to 800 N/mm² hardness, cast steel, non-ferrous metals, light metals, plastics, reinforced fabrics, plasterboard, and in light construction applications.

For optimal use, it is important to follow certain application guidelines. The hole saw is not suitable for hammer drilling, and it is recommended to apply light pressure when starting to drill. It is essential to maintain constant pressure and avoid oscillating movements during the process.

Additionally, the use of coolant is suggested to improve performance and extend tool life.

- Diameter: Ø 33 mm
- Material thickness: up to 2.5 mm
- Cutting depth: 5.0 mm
- Right-hand cutting
- Resharpenable
- Recommended for alloy steels (up to 800 N/mm²)
- Suitable for non-ferrous and light metals
- Compatible with plastics and reinforced fabrics
- Not suitable for hammer drilling
- Use of coolant recommended

Specifications

High	5,00
Width	5,00
EAN	4007140294883
Manufacturer	Ruko
Weight (kg)	0,1300
Depth	12,00

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 2 October 2026