

Product sheet

RUKO 40mm diameter high precision HSS-G core drill bit.

Brand: Ruko

Reference: TUR 128040

The Ruko-128040 HSS-G (Ø 40 mm) hole saw is ideal for materials up to 2.5 mm thick. Its design allows for precise cutting of alloy steels, non-ferrous metals, and plastics, with a cutting depth of 5 mm.

[View product online](#)

Description

The Ruko-128040-HSS-G (Ø 40 mm) hole saw is a high-precision tool designed for drilling in a wide variety of materials. With a material thickness of up to 2.5 mm and a cutting depth of 5.0 mm, this hole saw is ideal for working with alloy steels, cast steel, non-ferrous metals, light metals, plastics, reinforced fabrics, plasterboard, and in light construction. Its right-hand cutting design allows for optimal performance, and its resharpenable design ensures a long service life and efficient operation.

It is important to note that this tool is not suitable for hammer drilling. For best results, it is recommended to apply light pressure when starting to drill, maintaining constant pressure and avoiding oscillating movements.

In addition, the use of coolant is advisable to prolong the tool's life and improve cut quality.

- **Diameter:** 40 mm
- **Material Thickness:** Up to 2.5 mm
- **Cutting Depth:** 5.0 mm
- **Cutting:** Right-handed
- **Resharpenable:** Yes
- **Recommended Materials:** Alloy steels, cast steel, non-ferrous metals, light metals, plastics, reinforced fabrics, plasterboard
- **Drilling Pressure:** Low and constant
- **Movements:** Avoid oscillations
- **Use of Coolant:** Recommended
- **Not suitable for:** Percussion drilling

Specifications

High	5,00
Width	5,00
EAN	4007140294951
Manufacturer	Ruko
Weight (kg)	0,1700
Depth	12,00

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 12 September 2026